



T-TAP[®]

T-TAP has been discontinued.
Please visit [product page](#) for current alternatives.

\$ US MSRP

<https://www.aja.com/products/t-tap>

Video Formats

- (2K) 2048 x 1080PsF 23.98, 24, 25 (4:2:2)
- (2K) 2048 x 1080p 23.98, 24, 25 (4:2:2)
- (HD) 1080i 50, 59.94, 60
- (HD) 1080PsF 23.98, 24
- (HD) 1080p 23.98, 24, 25, 29.97, 30
- (HD) 720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)

Video Outputs Digital

- 1.5G-SDI, SMPTE 292M
 - Single Link HD-SDI YCbCr 4:2:2 10-bit
- 270 Mbps SDI, SMPTE 259M-C
 - YCbCr 4:2:2 10-bit, 8-bit
- HDMI v1.3
 - 30-bits/pixel, RGB or YUV, 2.25 Gbps, SD, HD

*Bit depth support is application dependent. Check with your software manufacturer for compatibility.

Audio Outputs Digital

- 8-channel, 24-bit SMPTE-259 SDI embedded audio, 48 kHz sample rate, synchronous
- 8-channel, 24-bit HDMI embedded audio, 48 kHz sample rate, synchronous

Size (w x d x h)

- 2.95" x 0.7" x 2.28" (74.93 x 17.78 x 57.92 mm)

Weight

- 0.2 lb (0.1 kg)

Power

- 5V Thunderbolt bus powered; 6.5W max

Environment