



Product: <u>1311A</u> ☑

Speaker Cable, 2 C #12 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 2 Conductor 12 AWG (168 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

	Product Overview								
Suitable Applications: Speaker Cable; Direct Burial; Indoor/Outdoor Home Theater; In-Wall Speaker; Outdoor Speaker									
Construction Details									
Conductor									
Element Conductor(s)	Number of Elemen	t Size St 12 AWG 16	randing	Materia BC - Bare Copper (Hig					
Conductor(s)	2	12 AVIG 10	07.04	DC - Dale Copper (Hig	in conductivity)				
Insulation									
Element	Material	Nom. Thickne		n. Insulation Diameter					
Conductor(s)	PE - Polyethylene	0.018 in (0.46 m	nm) 0.14	l in (3.6 mm)	Black, Red				
Outer Jacket									
Materi	ial Nom. Ti	hickness No	om. Diam	neter					
PVC - Polyviny	yl Chloride 0.036 in	(0.91 mm) 0.38	52 in (8.9	4 mm)					
Overall Cable	Diameter (Nominal):	0.352 in (8.94	mm)						
Electrical C	Characteristics								
Electricals									
Element	Nom. Conducto	r DCR Nor	m. Capac	itance Cond-to-Cond	Nom. Velocity of Pro	p. Max. Current			
	Nom. Conducto 1.6 Ohm/1000ft (5.2			titance Cond-to-Cond 3.2 pF/m)	Nom. Velocity of Pro	p. Max. Current 17 Amps per conductor @ 25°C			
Conductor(s)									
Conductor(s)	1.6 Ohm/1000ft (5.2								
Conductor(s) Voltage	1.6 Ohm/1000ft (5.2								
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL	1.6 Ohm/1000ft (5.2 ating _3)	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL	1.6 Ohm/1000ft (5.2	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanica	1.6 Ohm/1000ft (5.2 ating _3)	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanica Temperature UL Temperatu	1.6 Ohm/1000ft (5.2 ating L3) I Characteristic	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanica Temperature	1.6 Ohm/1000ft (5.2 ating .3) I Characteristic	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanical Temperature UL Temperatu 75°C	1.6 Ohm/1000ft (5.2 ating L3) I Characteristic	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanical Temperature UL Temperatu 75°C	1.6 Ohm/1000ft (5.2 ating .3) I Characteristic ure Operating -20°C To +75°C	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanical Temperature UL Temperatu 75°C Bend Radius	1.6 Ohm/1000ft (5.2 ating .3) I Characteristic ure Operating -20°C To +75°C n. Installation Min.	Ohm/km) 22.3							
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanical Temperature UL Temperatur 75°C Bend Radius Stationary Mil	1.6 Ohm/1000ft (5.2 ating L3) I Characteristic UTE Operating -20°C To +75°C n. Installation Min.) 3.5 in (89 mm)	Ohm/km) 22.3	3 pF/ft (73						
Conductor(s) Voltage UL Voltage Ra 300 V (CM, CL Mechanical Temperature UL Temperatu 75°C Bend Radius Stationary Mii 3.5 in (89 mm)	1.6 Ohm/1000ft (5.2 ating .3) I Characteristic ure Operating -20°C To +75°C n. Installation Min.) 3.5 in (89 mm) sion:	Ohm/km) 22.3	3 pF/ft (73	3.2 pF/m)					

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor
Flammability / Reaction to Fire:	UL1666 Riser, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	СМ
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6000UE

Product Notes

Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

History

Update and Revision:

Revision Number: 0.335 Revision Date: 04-08-2022

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC
1311A 010500	Black	Reel	500 ft	612825111610
1311A 0101000	Black	Reel	1,000 ft	612825111603
1311A 008500	Gray	Reel	500 ft	612825111597
1311A 0081000	Gray	Reel	1,000 ft	612825111580
1311A 1SL500	White 1SL	Reel	500 ft	612825111634
1311A 1SL1000	White 1SL	Reel	1,000 ft	612825111627

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.