

## 1810A Multi-Conductor - High Flex Multi-Conductor Cable Bi-amp & Tri-amp Spkr Conn



For more Information  
please call

1-800-Belden1



### General Description:

14 AWG stranded (104x34) bare copper conductors, PVC insulation, conductors cabled with fillers, paperwrap, overall PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material
4	14	104x34	BC - Bare Copper

Total Number of Conductors: 4

#### Insulation

##### Insulation Material:

Insulation Material	Dia. (mm)
PVC - Polyvinyl Chloride	3.175

#### Outer Shield

##### Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Cabling Fillers: Polypropylene

##### Overall Cabling Color Code Chart:

Number	Color
1	Red
2	Green
3	White
4	Black

Overall Cabling Separator Material: Paper Tape

Overall Cabling Separator Thickness: 0.051 mm

Overall Nominal Diameter: 9.906 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Non-UL Temperature Rating: 60°C

Bulk Cable Weight: 156.261 Kg/Km

Max. Recommended Pulling Tension: 889.640 N

Min. Bend Radius/Minor Axis: 101.600 mm

## 1810A Multi-Conductor - High Flex Multi-Conductor Cable Bi-amp & Tri-amp Spkr Conn

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance (µH/m)
0.6562

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
60.6985

#### Nom. Cap. Between Cond. in a Quad Config.:

Capacitance (pF/m)
187.017

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
8.8587

#### Max. Operating Voltage - Non-UL:

Voltage
300 V RMS

#### Max. Recommended Current:

Current
9.5 Amps per conductor @ 25°C

### Notes (Overall)

Notes: Suggested Connectors: Neutrik Speakon®.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1810A B591000	1,000 FT	114.000 LB	BLACK, MATTE	C	4 #14 PVC PVC
1810A B59250	250 FT	28.000 LB	BLACK, MATTE	C	4 #14 PVC PVC
1810A B59500	500 FT	55.500 LB	BLACK, MATTE	C	4 #14 PVC PVC

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 10-17-2012

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications

## METRIC MEASUREMENT VERSION

### 1810A Multi-Conductor - High Flex Multi-Conductor Cable Bi-amp & Tri-amp Spkr Conn

described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).