



**Product:** <u>5541P1</u> ☑

Security & Sound, #22-2pr, BC, Indiv. Foil, CM, Water-Blocked

## **Product Description**

Security & Sound Cable, Riser-CM, 2-22 AWG stranded bare copper pairs with PVC insulation, Individually Waterblock tape and Beldfoil® shielded, PVC jacket

## **Technical Specifications**

Suitable /	Applications:	S	ecurity Systen	, Intercom	/PA, Audio/Speak	er, Power-Limit	ed Controls, Noisy &
Constru	uction Deta	ails					
Conducto	r						
Element	Number of E	lement Siz	ze Strandi	ng M	aterial		
Pair(s)	2	22 A	WG 7x30	BC - B	Bare Copper		
Insulation	ı						
Element	Mate	rial	Nom. Thickno	ss Nom	. Insulation Dian	neter (	Color Code
Pair(s)	PVC - Polyvir	yl Chloride (	0.010 in (0.25	nm) 0.049	9 in (1.2 mm)	Black & \	Vhite, Green & Red
Inner Shie	eld						
Element	Shield Type	Mat	erial	Coverage	Drainwire Ty	pe Notes	
Pair(s)	Таре	Bi-Laminate	(Alum+Poly)	100%	24 AWG (7x32)	TC each pair	
Waterblo	cking:	٧	/aterblock Tap	е			
Outer Jac	ket						
IV	laterial	Nom. Thic	kness No	n. Diamet	er		
	la a sina al Olada ni da	0.025 in (0.	64 mm) 0.23	) in (6 07 n	nm)		

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.025 in (0.64 mm)	0.239 in (6.07 mm)
Overall Cable Diameter (Nominal): 0.239 in (6.07 mm)		

# **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Pair(s)	16.4 Ohm/1000ft	47.2 pF/ft (155 pF/m)	84.9 pF/ft (279 pF/m)	3.8 Amps per conductor @ 25°C

## Voltage

**UL Voltage Rating** 300 V (CM)

#### **Mechanical Characteristics**

# Temperature

<b>UL Temperature</b>	Operating
105°C	-20°C To +105°C

### Bend Radius

Stationary Min.	Installation Min.
2.4 in (61 mm)	2.4 in (61 mm)

Max. Pull Tension:	42 lbs (19 kg)
Bulk Cable Weight:	27 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Reaction to Fire:	UL 1685 FT4 Loading
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CM
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### History

Update and Revision:	Revision Number: 0.439 Revision Date: 01-20-2023	

### **Part Numbers**

#### Variants

Item #	Color	UPC
5541P1 0101000	Black	612825164289
5541P1 0081000	Gray	612825164272

© 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.